

INDUSTRIAL COMPONENT DATA

DILK12-11(415V50HZ,480V60HZ) 293991 Y7-293991 EATON ELECTRIC Contactor for 3-phase/three-phase capacitors, 1..

Brand: EATON - MOELLER | Manufacturer Part Number: DILK12-11(415V50HZ,480V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILK12-11(415V50HZ,480V60HZ)
Catalog number	Y7-293991
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-7CA197EFD4
Generated	2026-08-05

Product Overview

Contactor for 3-phase/three-phase capacitors, 12.5kVAR

DILK12-11(415V50HZ,480V60HZ)

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 12.5 kVAr, 415 V 50 Hz, 480 V 60 Hz

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILK capacity contactor Catalog Number 293991 Model Code

DILK12-11(415V50HZ,480V60HZ) EAN 4015082939915 Product Length/Depth 138 mm Product Height 135 mm Product Width 45 mm Product Weight 0.51 kg Certifications CSA C22.2.

UL Listed

IEC 60947-4-1

EN 60947-4-1

CSA File No.: 012528

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

IEC/EN 60947

CE

UL
CSA
CSA Class No.: 3211-04
UL 60947-4-1
UL Category Control No.: NLDX Features & Functions
Fitted with: Series resistors General
Application Contactors for power factor correction Lifespan, electrical 150,000 Operations Operating frequency 120
Operations/h Product category DILK Contactors for capacitors Protection Finger and back-of-hand proof, Protection against
direct contact when actuated from front (EN 50274) Voltage type AC Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Electro Magnetic Compatibility
Emitted interference According to EN 60947-1 Interference immunity According to EN 60947-1 Terminal capacities
Terminal capacity (flexible with ferrule) 1 x (0.75 - 16) mm², Main cables Terminal capacity (solid) 1 x (0.75 - 16) mm², Main
cables Terminal capacity (solid/stranded AWG) 18 - 6, Main cables Terminal capacity (stranded) 1 x 16 mm², Main cables
Electrical Rating
Rated operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILK12-11(415V50HZ,480V60HZ) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.