

INDUSTRIAL COMPONENT DATA

DILAC-22(24V50HZ) 276495 XTREC10B22U EATON ELECTRIC

Contactor relay, 2N/O+2N/C, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-22(24V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-22(24V50HZ)
Catalog number	XTREC10B22U
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-BACFA7DCF4
Generated	2026-08-04

Product Overview

Contactor relay, 2N/O+2N/C, AC

Auxiliary Contactor 2 NO + 2 NC Push-in connection 24 V 50 Hz

Contactor relay, 24 V 50 Hz, 2 N/O, 2 NC, Spring-loaded terminals, AC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 24 V 50 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005 , Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

Contactor relay, 24 V 50 Hz, 2 N/O, 2 NC, Spring-loaded terminals, AC operationContactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 24 V 50 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal

markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILA relays Application Contactor relays Description Basic devices with positive operation contacts Connection technique Spring-loaded terminals Rated operational current AC-15 220 V 230 V 240 V [Ie]4 AAC-15 380 V 400 V 415 V [Ie]4 A Contacts N/O = Normally open 2 N/ON/C = Normally closed 2 NC Contact sequence Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005 Code number and version of combination Distinctive number 22D Can be combined with auxiliary contact module DILA-XHIC(V)... Actuating voltage 24 V 50 Hz Voltage AC/DC AC operation Connection to SmartWire-DT no Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005 Technical data

General Standards IEC/EN 60947, EN 60947...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-22(24V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.