

**INDUSTRIAL COMPONENT DATA**

# DILER-22-G(60VDC) 010499 EATON ELECTRIC Contactor relay, 2N/O+2N/C, DC current

Brand: EATON - MOELLER | Manufacturer Part Number: DILER-22-G(60VDC)



|                 |                   |
|-----------------|-------------------|
| Manufacturer    | EATON - MOELLER   |
| MPN / Reference | DILER-22-G(60VDC) |
| Catalog number  | 010499            |
| Category        | Contactor relay   |
| Minimum order   | 1 Pcs             |
| Document ID     | EO-6FBDE590D9     |
| Generated       | 2026-07-29        |

## Product Overview

Contactor relay, 2N/O+2N/C, DC current

Mini-Contactor Auxiliary; Connection screw; 2 NO + 2 NC; 60 V DC

Contactor relay, 60 V DC, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Screw terminals, DC operation

Contactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current, 1 pole

Open at 50 °C: I<sub>th</sub> = I<sub>e</sub> = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I<sub>e</sub> = 6 A, 380 V 400 V 415 V: I<sub>e</sub> = 3 A,

Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination

Distinctive number: 22E, Actuating voltage: 60 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20,

Instructions: Contact numbers to EN 50011 , Coil terminal markings to EN 50005, Integrated diode-resistor combination,

Coil rating 2.6 W, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

## Additional Product Information

Contactor relay, 60 V DC, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Screw terminals, DC

operationContactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current,

1 pole Open at 50 °C: I<sub>th</sub> = I<sub>e</sub> = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I<sub>e</sub> = 6 A, 380 V 400 V 415 V: I<sub>e</sub> = 3 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination

Distinctive number: 22E, Actuating voltage: 60 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20,

Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Integrated diode-resistor combination, Coil rating 2.6 W, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILER Mini-contactors Application Contactor relays Description with interlocked opposing contacts Connection technique Screw terminals Rated operational current Conventional free air thermal current, 1 pole Open at 50 °C [ $I_{th}=I_e$ ] 10 AAC-15220 V 230 V 240 V [ $I_e$ ] 6 AAC-15380 V 400 V 415 V [ $I_e$ ] 3 A Contacts N/O = Normally open 2 N/ON/C = Normally closed 2 NC Contact sequence Code number and version of combination Distinctive number 22E Actuating voltage 60 V DC Voltage AC/DC DC operation Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005

Integrated diode-resistor combination...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILER-22-G(60VDC) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.