

INDUSTRIAL COMPONENT DATA

DILA-22(*VDC) 276419 EATON ELECTRIC Control relays, 12VDC, 8 DI(2 AI), 4 DO relays, Clock

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-22(*VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-22(*VDC)
Catalog number	-
Category	Contacteur relay
Minimum order	10 Pcs
Document ID	EO-BC072D7B9B
Generated	2026-08-02

Product Overview

Control relays, 12VDC, 8 DI(2 AI), 4 DO relays, Clock

Auxiliary Contactor; 2 NO + 2 NC; Screw connection; * VDC

Contacteur relay, *V DC, 2 N/O, 2 NC, Screw terminals, DC operation

Contacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: *V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005 , built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contacteur relay, *V DC, 2 N/O, 2 NC, Screw terminals, DC operationContacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: *V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005 ,

built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

General specificationsProduct nameEaton Moeller® series DILA Control RelayPart no.DILA-22(*VDC)Product

Length/Depth75 millimetreProduct height68 millimetreProduct width45 millimetreProduct weight0.294

kilogramCertificationsCSA

UL Category Control No.: NKCR

UL File No.: E29184

UL 508

CSA-C22.2 No. 14-05

IEC/EN 60947-4-1

VDE 0660

CSA Class No.: 3211-03

CSA File No.: 012528

EN 60947-5-1

UL

CE

IEC/EN 60947Product TradenameDILAProduct TypeControl RelayProduct Sub TypeNoneCatalog NotesCoil terminal

markings according to EN 50005

Contact numbers according to EN 50011

Minimum order quantity 10 items (packaging unit)

Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specifi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-22(*VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.