

INDUSTRIAL COMPONENT DATA

DILAC-22(110VDC) 276523 XTREC10B22E0 EATON ELECTRIC

Contacteur relay, 2N/O+2N/C, DC current

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-22(110VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-22(110VDC)
Catalog number	XTREC10B22E0
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-AAD38D2D77
Generated	2026-08-02

Product Overview

Contacteur relay, 2N/O+2N/C, DC current

Auxiliary Contacteur 2 NO + 2 NC Pressure connection 110 VDC

Contacteur relay, 110 V DC, 2 N/O, 2 NC, Spring-loaded terminals, DC operation

Contacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 110 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005 , built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contacteur relay, 110 V DC, 2 N/O, 2 NC, Spring-loaded terminals, DC operationContacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 110 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal

markings to EN 50005 , built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

General specificationsProduct nameEaton Moeller® series DILA Control RelayPart

no.DILAC-22(110VDC)EAN4015082765231Product Length/Depth75 millimetreProduct height68 millimetreProduct width45 millimetreProduct weight0.286 kilogramCompliancesCE MarkedCertificationsIEC 60947-4-1

UL 508

CSA Std. C22.2 No. 14-05

EN 60947-4-1

VDE

CSA File No.: 012528

CSA

CE

UL Category Control No.: NKCR

UL File No.: E29184

UL

CSA-C22.2 No. 14-05

CSA Class No.: 3211-03

VDE 0660

EN 60947-5-1

IEC/EN 60947-4-1

IEC/EN 60947Product TradenameDILAProduct TypeControl RelayProduct Sub TypeNoneCatalog NotesThis item can only be ordered until December 31, 2023 with a maximum delivery date of May 31, 2024.Features & Functio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-22(110VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.