

INDUSTRIAL COMPONENT DATA

DILAC-22(*VDC) 276525 EATON ELECTRIC Control relays, 12VDC, 8 DI(2 AI), 4 DO relays, Clock

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-22(*VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-22(*VDC)
Catalog number	276525
Category	Contacteur relay
Minimum order	10 Pcs
Document ID	EO-B45F4FF3D3
Generated	2026-08-04

Product Overview

Control relays, 12VDC, 8 DI(2 AI), 4 DO relays, Clock

Auxiliary contactor; 2 NO + 2 NC; Snap-in connection; *VDC

Contacteur relay, *V DC, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Spring-loaded terminals, DC operation

Contacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive

operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V:

Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code

number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module:

DILA-XHIC(V)..., Actuating voltage: *V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact

numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit, Standards: IEC/EN 60947, EN

60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contacteur relay, *V DC, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Spring-loaded terminals, DC

operationContacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive

operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V:

Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code

number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module:

DILA-XHIC(V)..., Actuating voltage: *V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact

numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILA relays Application Contactor relays Description Basic devices with positive operation contacts Connection technique Spring-loaded terminals Rated operational current AC-15 220 V 230 V 240 V [Ie]4 AAC-15 380 V 400 V 415 V [Ie]4 A Contacts N/O = Normally open 2 N/ON/C = Normally closed 2 NC Contact sequence Code number and version of combination Distinctive number 22 DC Can be combined with auxiliary contact module DILA-XHIC(V)... Actuating voltage *V DC Voltage AC/DC DC operation Suppressor circuit built-in Connection to SmartWire-DT no Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005

built-in suppressor circuit'

Integrated v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-22(*VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.