

INDUSTRIAL COMPONENT DATA

DILA-31(380V50/60HZ) 276373 XTRE10B31AR EATON

ELECTRIC Contactor relay, 3N/O+1N/C, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-31(380V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-31(380V50/60HZ)
Catalog number	XTRE10B31AR
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-B47900D568
Generated	2026-08-05

Product Overview

Contactor relay, 3N/O+1N/C, AC

Auxiliary Contactor 3 NO + 1 NC Screw connection 380 V 50/60HZ

Contactor relay, 380 V 50/60 Hz, 3 N/O, 1 NC, Screw terminals, AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor relay, 380 V 50/60 Hz, 3 N/O, 1 NC, Screw terminals, AC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: I_e= 4 A, 380 V 400 V 415 V: I_e= 4 A, Contacts N/O = Normally open: 3 N/O, Contacts N/C = Normally closed: 1 NC, Code number and version of combination Distinctive number: 31E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 380 V 50/60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

Delivery program

Product rangeDILA relaysApplicationContactor relaysDescriptionBasic devices with positive operation contactsConnection techniqueScrew terminalsRated operational currentAC-15220 V 230 V 240 V [I_e]4 AAC-15380 V 400 V 415 V [I_e]4 AContactsN/O = Normally open3 N/ON/C = Normally closed1 NCContact sequenceInstructionsContact numbers to EN 50011

Coil terminal markings to EN 50005Code number and version of combinationDistinctive number31ECan be combined with auxiliary contact moduleDILA-XHI(V)...Actuating voltage380 V 50/60 HzVoltage AC/DCAC operationConnection to

SmartWire-DT no instructions Contact numbers to EN 50011
Coil terminal markings to EN 50005 Technical data
General Standards IEC/EN 60947, EN 60947-5-1, VDE 0660...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-31(380V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.