

## INDUSTRIAL COMPONENT DATA

# DILAC-31(\*V60HZ) 276486 EATON ELECTRIC Star-delta contactor combination, 132kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-31(\*V60HZ)



|                 |                  |
|-----------------|------------------|
| Manufacturer    | EATON - MOELLER  |
| MPN / Reference | DILAC-31(*V60HZ) |
| Catalog number  | -                |
| Category        | Contactor relay  |
| Minimum order   | 10 Pcs           |
| Document ID     | EO-2D1A228CE1    |
| Generated       | 2026-08-04       |

## Product Overview

Star-delta contactor combination, 132kW/400V/AC3

Auxiliary contactor; 3 NO + 1 NC; Snap-in connection; \* V 60 Hz

Contactor relay, \*V 60 Hz, 3 N/O, 1 NC, Spring-loaded terminals, AC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 3 N/O, Contacts N/C = Normally closed: 1 NC, Code number and version of combination Distinctive number: 31E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: \*V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

## Additional Product Information

Contactor relay, \*V 60 Hz, 3 N/O, 1 NC, Spring-loaded terminals, AC operationContactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 3 N/O, Contacts N/C = Normally closed: 1 NC, Code number and version of combination Distinctive number: 31E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: \*V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal

markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILA relays Application Contactor relays Description Basic devices with positive operation contacts Connection technique Spring-loaded terminals Rated operational current AC-15 220 V 230 V 240 V [I<sub>e</sub>]4 AAC-15 380 V 400 V 415 V [I<sub>e</sub>]4 A Contacts N/O = Normally open 3 N/ON/C = Normally closed 1 NC Contact sequence Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005 Code number and version of combination Distinctive number 31E Can be combined with auxiliary contact module DILA-XHIC(V)... Actuating voltage \*V 60 Hz Voltage AC/DC AC operation Connection to SmartWire-DT no Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005 Note on equipment supplied Minimum order quantity 10 items (...)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-31(\*V60HZ) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.