

INDUSTRIAL COMPONENT DATA

DILAC-31(220VDC) 276492 XTREC10B31BD EATON ELECTRIC

Contactor relay, 3N/O+1N/C, DC current

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-31(220VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-31(220VDC)
Catalog number	XTREC10B31BD
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-3162BC479C
Generated	2026-08-03

Product Overview

Contactor relay, 3N/O+1N/C, DC current

Auxiliary contactor; 3 NO + 1 NC; Snap-in connection; 220 VDC

Contactor relay, 220 V DC, 3 N/O, 1 NC, Spring-loaded terminals, DC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 3 N/O, Contacts N/C = Normally closed: 1 NC, Code number and version of combination Distinctive number: 31E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 220 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005 , built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

Contactor relay, 220 V DC, 3 N/O, 1 NC, Spring-loaded terminals, DC operation Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 3 N/O, Contacts N/C = Normally closed: 1 NC, Code number and version of combination Distinctive number: 31E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 220 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal

markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILA relays Application Contactor relays Description Basic devices with positive operation contacts Connection technique Spring-loaded terminals Rated operational current AC-15 220 V 230 V 240 V [Ie]4 AAC-15 380 V 400 V 415 V [Ie]4 A Contacts N/O = Normally open 3 N/ON/C = Normally closed 1 NC Contact sequence Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005

built-in suppressor circuit'

Integrated varistor suppressor circuit. Code number and version of combination Distinctive number 31E Can be combined with auxiliary contact module DILA-XHIC(V)... Actuating voltage 220 V DC Voltage AC/DC CDC operation Suppressor circuit built-in Connection to SmartWire-DT no Instruct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-31(220VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.