

INDUSTRIAL COMPONENT DATA

DILER-40(115V60HZ) 010270 XTRM10A40CX EATON

ELECTRIC Contactor relay, 4N/O, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILER-40(115V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILER-40(115V60HZ)
Catalog number	XTRM10A40CX
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-2AB20639F1
Generated	2026-08-03

Product Overview

Contactor relay, 4N/O, AC

Mini-Contactor Auxiliary; Connection screw; 4 NO; 115 V 60 Hz

Contactor relay, 115V 60 Hz, N/O = Normally open: 4 N/O, Screw terminals, AC operation

Contactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current, 1 pole Open at 50 °C: I_{th} = I_e = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I_e = 6 A, 380 V 400 V 415 V: I_e = 3 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40 E, For use with: ...DILE, Actuating voltage: 115V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Contactor relay, 115V 60 Hz, N/O = Normally open: 4 N/O, Screw terminals, AC operationContactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current, 1 pole Open at 50 °C: I_{th} = I_e = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I_e = 6 A, 380 V 400 V 415 V: I_e = 3 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40 E, For use with: ...DILE, Actuating voltage: 115V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

Delivery program

Product rangeDILER Mini-contactorsApplicationContactor relaysDescriptionwith interlocked opposing contactsConnection techniqueScrew terminalsRated operational currentConventional free air thermal current, 1 poleOpenat 50 °C [I_{th}=I_e]10 AAC-15220 V 230 V 240 V [I_e]6 AAC-15380 V 400 V 415 V [I_e]3 AContactsN/O = Normally open4 N/OContact sequenceCode number and version of combinationDistinctive number40 EFor use with...DILEActuating voltage115V 60 HzVoltage AC/DCAC operationInstructionsContact numbers to EN 50011
Coil terminal markings to EN 50005Technical data
GeneralStandardsIEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSALifespan, mechanicalAC operated [Operations]10 x 106Maximum ope...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILER-40(115V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.