

INDUSTRIAL COMPONENT DATA

DILA-40(24V60HZ) 276320 XTRE10B40B6 EATON ELECTRIC

Contacteur relay, 4N/O, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-40(24V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-40(24V60HZ)
Catalog number	XTRE10B40B6
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-19B403666B
Generated	2026-08-06

Product Overview

Contacteur relay, 4N/O, AC

Auxiliary Contacteur 4 NO Screw Connection 24 V 60 Hz

Contacteur relay, 24 V 60 Hz, 4 N/O, Screw terminals, AC operation

Contacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 24 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contacteurs up to 170A
--------------	--

Additional Product Information

Contacteur relay, 24 V 60 Hz, 4 N/O, Screw terminals, AC operationContacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 24 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA
Delivery program

Product rangeDILA relaysApplicationContactor relaysDescriptionBasic devices with positive operation contactsConnection techniqueScrew terminalsRated operational currentAC-15220 V 230 V 240 V [Ie]4 AAC-15380 V 400 V 415 V [Ie]4 AContactsN/O = Normally open4 N/OContact sequenceInstructionsContact numbers to EN 50011
Coil terminal markings to EN 50005Code number and version of combinationDistinctive number40ECan be combined with auxiliary contact moduleDILA-XHI(V)...Actuating voltage24 V 60 HzVoltage AC/DCAC operationConnection to SmartWire-DTnoInstructionsContact numbers to EN 50011
Coil terminal markings to EN 50005Technical data
GeneralStandardsIEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSALifespan, mechanicalAC operated [Operations]20 x 106Maximum operating fr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-40(24V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.