

INDUSTRIAL COMPONENT DATA

DILA-40(600V60HZ) 276324 XTRE10B40K6 EATON ELECTRIC

Contactor relay, 4N / O, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-40(600V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-40(600V60HZ)
Catalog number	XTRE10B40K6
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-A4F408ABDC
Generated	2026-08-04

Product Overview

Contactor relay, 4N / O, AC

Auxiliary contactor; 4 NO; Screw connection; 600 V 60 Hz

Contactor relay, 600 V 60 Hz, 4 N/O, Screw terminals, AC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 600 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL , CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

Contactor relay, 600 V 60 Hz, 4 N/O, Screw terminals, AC operationContactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 600 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA
Delivery program

Product range DILA relays Application Contactor relays Description Basic devices with positive operation contacts Connection technique Screw terminals Rated operational current AC-15 220 V 230 V 240 V [I_e]4 AAC-15 380 V 400 V 415 V [I_e]4 A Contacts N/O = Normally open 4 N/O Contact sequence Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 Code number and version of combination Distinctive number 40E Can be combined with auxiliary contact module DILA-XHI(V)... Actuating voltage 600 V 60 Hz Voltage AC/DC AC operation Connection to SmartWire-DT no Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 Technical data General Standards IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Lifespan, mechanical AC operated [Operations] 20 x 10⁶ Maximum operating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-40(600V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.