

## INDUSTRIAL COMPONENT DATA

# DILA-40(415V50HZ,480V60HZ) 276332 Y7-276332 EATON ELECTRIC Contactor relay, 4N/O, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-40(415V50HZ,480V60HZ)



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | EATON - MOELLER            |
| MPN / Reference | DILA-40(415V50HZ,480V60HZ) |
| Catalog number  | Y7-276332                  |
| Category        | Contactor relay            |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-50C5FC05C1              |
| Generated       | 2026-08-05                 |

## Product Overview

Contactor relay, 4N/O, AC

DILA-40(415V50HZ,480V60HZ)

Eaton Moeller® series DILA Contactor relay, 415 V 50 Hz, 480 V 60 Hz, 4 N/O, Screw terminals, AC operation

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Contactors up to 170A

## Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Control relay Catalog Number 276332 Model Code

DILA-40(415V50HZ,480V60HZ) EAN 4015082763329 Product Length/Depth 75 mm Product Height 68 mm Product Width 45 mm Product Weight 0.237 kg Certifications CSA

UL 508

VDE 0660

CSA-C22.2 No. 14-05

IEC/EN 60947

CE

CSA File No.: 012528

UL File No.: E29184

EN 60947-5-1

UL

UL Category Control No.: NKCR

CSA Class No.: 3211-03

IEC/EN 60947-4-1 Features & Functions

Features Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module Fitted with: Positive operation contacts General

Application Contactor relays Degree of protection IP20 Shock resistance 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, mechanical 20,000,000 Operations (AC operated) Mounting method DIN-rail/screw

Connection Screw terminals Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Product category DILA relays Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front

(EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambien...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-40(415V50HZ,480V60HZ) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.