

INDUSTRIAL COMPONENT DATA

DILA-40(24V50/60HZ) 276333 Y7-276333 EATON ELECTRIC

Contacteur relay, 4N / O, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-40(24V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-40(24V50/60HZ)
Catalog number	Y7-276333
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-170A2B3BC1
Generated	2026-08-05

Product Overview

Contacteur relay, 4N / O, AC

DILA-40(24V50/60HZ)

Contacteur relay, 24 V 50/60 Hz, 4 N/O, Screw terminals, AC operation

Contacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40D, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 24 V 50/60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL , CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contacteurs up to 170A

Additional Product Information

Contacteur relay, 24 V 50/60 Hz, 4 N/O, Screw terminals, AC operationContacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40D, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 24 V 50/60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSADelivery program

Product range DILA relays Application Contactor relays Description Basic devices with positive operation contacts Connection technique Screw terminals Rated operational current AC-15 220 V 230 V 240 V [I_e]4 AAC-15 380 V 400 V 415 V [I_e]4 A Contacts N/O = Normally open 4 N/O Contact sequence Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 Code number and version of combination Distinctive number 40 D Can be combined with auxiliary contact module DILA-XHI(V)... Actuating voltage 24 V 50/60 Hz Voltage AC/DC AC operation Connection to SmartWire-DT no Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 Technical data General Standards IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Lifespan, mechanical AC operated [Operations] 20 x 10⁶ Maximum ope...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-40(24V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.