

INDUSTRIAL COMPONENT DATA

DILA-40(380V50/60HZ) 276338 XTRE10B40AR EATON ELECTRIC 276338 DILA-40(380V50/60HZ)

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-40(380V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-40(380V50/60HZ)
Catalog number	XTRE10B40AR
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-01BF656770
Generated	2026-08-05

Product Overview

276338 DILA-40(380V50/60HZ)

Auxiliary Contactor 4 NO Screw Connection 380 V 50/60HZ

Contactor relay, 380 V 50/60 Hz, 4 N/O, Screw terminals, AC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 380 V 50/60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL , CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor relay, 380 V 50/60 Hz, 4 N/O, Screw terminals, AC operation Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 380 V 50/60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product rangeDILA relaysApplicationContactor relaysDescriptionBasic devices with positive operation contactsConnection techniqueScrew terminalsRated operational currentAC-15220 V 230 V 240 V [Ie]4 AAC-15380 V 400 V 415 V [Ie]4 AContactsN/O = Normally open4 N/OContact sequenceInstructionsContact numbers to EN 50011
Coil terminal markings to EN 50005Code number and version of combinationDistinctive number40ECan be combined with auxiliary contact moduleDILA-XHI(V)...Actuating voltage380 V 50/60 HzVoltage AC/DCAC operationConnection to SmartWire-DTnoInstructionsContact numbers to EN 50011
Coil terminal markings to EN 50005Technical data
GeneralStandardsIEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSALifespan, mechanicalAC operated [Operations]20 x 106Maximum....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-40(380V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.