

INDUSTRIAL COMPONENT DATA

DILA-40(380V50/60HZ) 276338 XTRE10B40AR EATON ELECTRIC 276338 DILA-40(380V50/60HZ)

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-40(380V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-40(380V50/60HZ)
Catalog number	XTRE10B40AR
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-01BF656770
Generated	2026-08-06

Product Overview

276338 DILA-40(380V50/60HZ)

Auxiliary Contactor 4 NO Screw Connection 380 V 50/60HZ

Contactor relay, 380 V 50/60 Hz, 4 N/O, Screw terminals, AC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 380 V 50/60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL , CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor relay, 380 V 50/60 Hz, 4 N/O, Screw terminals, AC operation Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: 380 V 50/60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILA relays Application Contactor relays Description Basic devices with positive operation contacts Connection technique Screw terminals Rated operational current AC-15 220 V 230 V 240 V [I_e]4 AAC-15 380 V 400 V 415 V [I_e]4 A Contacts N/O = Normally open 4 N/O Contact sequence Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 Code number and version of combination Distinctive number 40E Can be combined with auxiliary contact module DILA-XHI(V)... Actuating voltage 380 V 50/60 Hz Voltage AC/DC AC operation Connection to SmartWire-DT no Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 Technical data General Standards IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Lifespan, mechanical AC operated [Operations] 20 x 10⁶ Maximum....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-40(380V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.