

INDUSTRIAL COMPONENT DATA

DILAC-40(48V50HZ) 276432 XTREC10B40Y EATON ELECTRIC

Contact relay, 4N / O, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-40(48V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-40(48V50HZ)
Catalog number	XTREC10B40Y
Category	Contact relay
Minimum order	1 Pcs
Document ID	EO-2A81BA9897
Generated	2026-08-04

Product Overview

Contact relay, 4N / O, AC

Auxiliary Contactor; 4 NO; Snap-on connection; 48 V 50 Hz

Contact relay, 48 V 50 Hz, 4 N/O, Spring-loaded terminals, AC operation

Contact relay, Product range: DILA relays, Application: Contactor relays, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: I_e= 4 A, 380 V 400 V 415 V: I_e= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 48 V 50 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Contact relay, 48 V 50 Hz, 4 N/O, Spring-loaded terminals, AC operation
Contact relay, Product range: DILA relays, Application: Contactor relays, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: I_e= 4 A, 380 V 400 V 415 V: I_e= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 48 V 50 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA
General specifications
Product name Eaton Moeller® series DILA Control Relay
Part

no.DILAC-40(48V50HZ)EAN4015082764326Product Length/Depth75 millimetreProduct height68 millimetreProduct width45 millimetreProduct weight0.225 kilogramCompliancesCE MarkedCertificationsIEC 60947-4-1

EN 60947-4-1

CSA Std. C22.2 No. 14-05

UL 508

VDE

IEC/EN 60947

CSA

EN 60947-5-1

UL Category Control No.: NKCR

CSA File No.: 012528

UL

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

CE

IEC/EN 60947-4-1

VDE 0660

UL File No.: E29184Product TradenameDILAPProduct TypeControl RelayProduct Sub TypeNoneCatalog NotesThis item can only be ordered until December 31, 2023 with a maximum delivery date of May 31, 2024.

Features &

FunctionsFeaturesPositive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact moduleGeneral informationApplicationC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-40(48V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.