


INDUSTRIAL COMPONENT DATA

DILAC-40(110VDC) 276459 XTREC10B40E0 EATON ELECTRIC

Contacteur relay, 4N/O, DC current

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-40(110VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-40(110VDC)
Catalog number	XTREC10B40E0
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-EB471CB38A
Generated	2026-08-05

Product Overview

Contacteur relay, 4N/O, DC current

Auxiliary Contacteur; 4 NO; Snap-on connection; 110 VDC

Contacteur relay, 110 V DC, 4 N/O, Spring-loaded terminals, DC operation

Contacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 110 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contacteurs up to 170A
--------------	--

Additional Product Information

Contacteur relay, 110 V DC, 4 N/O, Spring-loaded terminals, DC operationContacteur relay, Product range: DILA relays, Application: Contacteur relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 110 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

General specifications
Product name Eaton Moeller® series DILA Control Relay
Part no. DILAC-40(110VDC) EAN4015082764593
Product Length/Depth 75 millimetre
Product height 68 millimetre
Product width 45 millimetre
Product weight 0.286 kilogram
Compliances CE Marked
Certifications EN 60947-4-1
UL 508
IEC 60947-4-1
CSA Std. C22.2 No. 14-05
VDE
CSA File No.: 012528
CSA-C22.2 No. 14-05
UL File No.: E29184
UL
VDE 0660
EN 60947-5-1
IEC/EN 60947
CE
CSA
UL Category Control No.: NKCR
IEC/EN 60947-4-1
CSA Class No.: 3211-03
Product Tradename DILA
Product Type Control Relay
Product Sub Type None
Catalog Notes This item can only be ordered until December 31, 2023 with a maximum delivery date of May 31, 2024.
Features & Functions Features Positive operating contacts to EN....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-40(110VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.