

INDUSTRIAL COMPONENT DATA

DILAC-40(*VDC) 276461 EATON ELECTRIC Contactor relay, 4N/O, DC current

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-40(*VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-40(*VDC)
Catalog number	276461
Category	Contactor relay
Minimum order	10 Pcs
Document ID	EO-88FE7BA7DD
Generated	2026-08-02

Product Overview

Contactor relay, 4N/O, DC current

Auxiliary Contactor; 4 NO; Snap-on connection; *VDC

Contactor relay, *V DC, 4 N/O, Spring-loaded terminals, DC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: *V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Contactor relay, *V DC, 4 N/O, Spring-loaded terminals, DC operationContactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40D, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: *V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

General specificationsProduct nameEaton Moeller® series DILA Control RelayPart no.DILAC-40(*VDC)Product Length/Depth75 millimetreProduct height68 millimetreProduct width45 millimetreProduct weight0.286

kilogramCertificationsUL Category Control No.: NKCR

UL 508

CSA Class No.: 3211-03

CE

CSA-C22.2 No. 14-05

UL File No.: E29184

IEC/EN 60947

EN 60947-5-1

IEC/EN 60947-4-1

UL

VDE 0660

CSA File No.: 012528

CSAProduct TradenameDILAProduct TypeControl RelayProduct Sub TypeNoneCatalog NotesThis item can only be ordered until December 31, 2023 with a maximum delivery date of May 31, 2024.Features & FunctionsFeaturesPositive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact moduleFitted with:Positive operation contacts Supp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-40(*VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.