

INDUSTRIAL COMPONENT DATA

DILAC-40(24VDC)-GVP 120944 XTREC10B40TD-B EATON

ELECTRIC Contactor relay, 4N/O, DC current, large packaging

Brand: EATON - MOELLER | Manufacturer Part Number: DILAC-40(24VDC)-GVP



Manufacturer	EATON - MOELLER
MPN / Reference	DILAC-40(24VDC)-GVP
Catalog number	XTREC10B40TD-B
Category	Contactor relay
Minimum order	84 Pcs
Document ID	EO-D310635C4F
Generated	2026-08-03

Product Overview

Contactor relay, 4N/O, DC current, large packaging

Auxiliary Contactor 4 NO Snap-On Connection 24 VDC Large Packaging

Contactor relay, 24 V DC, N/O = Normally open: 4 N/O, Spring-loaded terminals, DC operation, large packaging

Contactor relay, Product range: DILA relays, Application: Contactor relays, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: $I_e = 4$ A, 380 V 400 V 415 V: $I_e = 4$ A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 24 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Contactor relay, 24 V DC, N/O = Normally open: 4 N/O, Spring-loaded terminals, DC operation, large packaging Contactor relay, Product range: DILA relays, Application: Contactor relays, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: $I_e = 4$ A, 380 V 400 V 415 V: $I_e = 4$ A, Contacts N/O = Normally open: 4 N/O, Code number and version of combination Distinctive number: 40E, Can be combined with auxiliary contact module: DILA-XHIC(V)..., Actuating voltage: 24 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILA relays Application Contactor relays Connection technique Spring-loaded terminals Rated operational current AC-15220 V 230 V 240 V [Ie] 4 A AC-15380 V 400 V 415 V [Ie] 4 A Contacts N/O = Normally open 4 N/O Contact sequence Code number and version of combination Distinctive number 40E Can be combined with auxiliary contact module DILA-XHIC(V)... Actuating voltage 24 V DC Voltage AC/DC DC operation Suppressor circuit built-in Connection to SmartWire-DT yes in conjunction with DIL-SWD SmartWire DT contactor module Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 built-in suppressor circuit' Technical data General Standards IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Lifespan, mechanicalDC operate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAC-40(24VDC)-GVP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.