

INDUSTRIAL COMPONENT DATA

SL4-L-B 171331 Y7-171331 EATON ELECTRIC Continuous light, blue

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-L-B



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-L-B
Catalog number	Y7-171331
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-2DACA2A778
Generated	2026-08-01

Product Overview

Continuous light, blue

SL4-L-B

Eaton Moeller® series SL4 Ba15d continuous light module; blue

Continuous light module, Color Blue, without light elements, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: $U_e < 250$ V AC/DC, Type of light: Continuous light, Light elements: Filament lamp max. 4 W, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Continuous light module Catalog Number 171331 Model Code SL4-L-B EAN 4015081678686 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.037 kg

Certifications UL report applies to both US and Canada

CE

Certified by UL for use in Canada

UL 508

UL File No.: E29184

CSA Class No.: NKCR7

CSA-C22.2 No. 94-91

CSA-C22.2 No. 14-10

IEC/EN 60947-5-1

IEC/EN 60529

UL Category Control No.: NKCR

UL Catalog Notes Without light elements Features & Functions

Color Blue Enclosure color Black Functions Continuous light Light modules Filament lamp max. 4 W Number of modules
Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides) General

Connection to SmartWire-DT No Degree of protection NEMA 13

IP66 Lifespan, electrical 3,000 h Light type Continuous light Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting Method BA15d lamp socket Mounting position As required Overvoltage category

III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp)

4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Continuous light module Voltage type
AC/DC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat,
constant, to IEC 60068-2-78

Damp heat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-L-B with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.