

INDUSTRIAL COMPONENT DATA

SL7-L-B 171433 Y7-171433 EATON ELECTRIC Continuous light, blue

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-L-B



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-L-B
Catalog number	Y7-171433
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-860422C599
Generated	2026-08-01

Product Overview

Continuous light, blue

SL7-L-B

Eaton Moeller® series SL7 Ba15d continuous light module; blue

Continuous light module, Color Blue, without light elements, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: $U_e = < 250 \text{ V AC/DC}$, Type of light: Continuous light, Light elements: Filament lamp max. 7 W, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Continuous light module Catalog Number 171433 Model Code SL7-L-B EAN 4015081677658 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.075 kg

Certifications CSA-C22.2 No. 14-10

UL report applies to both US and Canada

CSA-C22.2 No. 94-91

Certified by UL for use in Canada

IEC/EN 60947-5-1

IEC/EN 60529

CE

UL File No.: E29184

UL Category Control No.: NKCR

CSA Class No.: NKCR7

UL 508

UL Catalog Notes Without light elements Features & Functions

Color Blue Enclosure color Black Functions Continuous light Light modules Filament lamp max. 7 W Number of modules
Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides) General

Connection to SmartWire-DT No Degree of protection IP66

NEMA 13 Lifespan, electrical 3,000 h Light type Continuous light Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting Method BA15d lamp socket Mounting position As required Overvoltage category III

Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000

V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Continuous light module Voltage type AC/DC Climatic environmental
conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat,
constant, to IEC 60068-2-78

Damp heat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-L-B with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.