

## INDUSTRIAL COMPONENT DATA

# SL4-L-G 171332 Y7-171332 EATON ELECTRIC Continuous light, green

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-L-G



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | EATON - MOELLER                 |
| MPN / Reference | SL4-L-G                         |
| Catalog number  | Y7-171332                       |
| Category        | Optical module for signal tower |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-4F6FDF1C34                   |
| Generated       | 2026-08-04                      |

## Product Overview

Continuous light, green

SL4-L-G

Eaton Moeller® series SL4 Ba15d continuous light module; green

Continuous light module, Color green, without light elements, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage:  $U_e < 250$  V AC/DC, Type of light: Continuous light, Light elements: Filament lamp max. 4 W, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Continuous light module Catalog Number 171332 Model Code SL4-L-G EAN 4015081678693 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.037 kg

Certifications IEC/EN 60947-5-1

UL report applies to both US and Canada

UL Category Control No.: NKCR

IEC/EN 60529

CE

Certified by UL for use in Canada

UL 508

CSA-C22.2 No. 94-91

UL

UL File No.: E29184

CSA-C22.2 No. 14-10

CSA Class No.: NKCR7 Catalog Notes Without light elements Features & Functions

Color Green Enclosure color Black Functions Continuous light Light modules Filament lamp max. 4 W Number of modules  
Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base) General

Connection to SmartWire-DT No Degree of protection IP66

NEMA 13 Lifespan, electrical 3,000 h Light type Continuous light Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting Method BA15d lamp socket Mounting position As required Overvoltage category

III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp)

4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Continuous light module Voltage type  
AC/DC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat,  
cyclic, to IEC 60068-2-30

Damp heat,...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-L-G with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.