

INDUSTRIAL COMPONENT DATA

SL4-L-A 171336 Y7-171336 EATON ELECTRIC Continuous light, orange

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-L-A



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-L-A
Catalog number	Y7-171336
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-A88E67A35A
Generated	2026-08-01

Product Overview

Continuous light, orange

SL4-L-A

Eaton Moeller® series SL4 Ba15d continuous light module; orange

Continuous light module, Color Orange, without light elements, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: $U_e < 250$ V AC/DC, Type of light: Continuous light, Light elements: Filament lamp max. 4 W, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Continuous light module Catalog Number 171336 Model Code SL4-L-A EAN 4015081678730 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.037 kg

Certifications Certified by UL for use in Canada

UL Category Control No.: NKCR

UL 508

IEC/EN 60529

UL report applies to both US and Canada

CSA Class No.: NKCR7

CE

CSA-C22.2 No. 14-10

CSA-C22.2 No. 94-91

UL

UL File No.: E29184

IEC/EN 60947-5-1 Catalog Notes Without light elements Features & Functions

Color Orange Enclosure color Black Functions Continuous light Light modules Filament lamp max. 4 W Number of modules
Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base) General

Connection to SmartWire-DT No Degree of protection NEMA 4X

IP66 Lifespan, electrical 3,000 h Light type Continuous light Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting Method BA15d lamp socket Mounting position As required Overvoltage category

III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp)

4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Continuous light module Voltage type
AC/DC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30

Damp heat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-L-A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.