

INDUSTRIAL COMPONENT DATA

SL4-L-Y 171335 Y7-171335 EATON ELECTRIC Continuous light, yellow

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-L-Y



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-L-Y
Catalog number	Y7-171335
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-B79105FA9B
Generated	2026-08-04

Product Overview

Continuous light, yellow

SL4-L-Y

Eaton Moeller® series SL4 Ba15d continuous light module; yellow

Continuous light module, Color yellow, without light elements, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: $U_e < 250$ V AC/DC, Type of light: Continuous light, Light elements: Filament lamp max. 4 W, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Continuous light module Catalog Number 171335 Model Code SL4-L-Y EAN 4015081678723 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.037 kg

Certifications UL Category Control No.: NKCR

UL 508

CSA Class No.: NKCR7

IEC/EN 60947-5-1

CE

UL report applies to both US and Canada

UL File No.: E29184

CSA-C22.2 No. 14-10

Certified by UL for use in Canada

CSA-C22.2 No. 94-91

IEC/EN 60529

UL Catalog Notes Without light elements Product specifications

Type Continuous light module Product Category SL signal towers Pollution degree 3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Connection to SmartWire-DT No Mounting Method BA15d lamp socket Rated impulse withstand voltage (Uimp) 4000 V AC Enclosure color Black Functions Continuous light Color Yellow Voltage type AC/DC Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required Degree of protection NEMA 4

IP66 Lamp type None Overvoltage category III Lifespan, electrical 3,000 h Light type Continuous light Light modules

Filament lamp max. 4 W Number of modules Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base) Power consumption Max. 4 W with the specified voltages Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Rated operational voltage (Ue) at AC - max 250 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-L-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.