

INDUSTRIAL COMPONENT DATA

EASY719-DC-RCX 274120 0004519777 EATON ELECTRIC

Control relay, 24 V DC, 12DI(4AI), 6DO relays, time, expanda..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY719-DC-RCX



Manufacturer	EATON - MOELLER
MPN / Reference	EASY719-DC-RCX
Catalog number	0004519777
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-3D4A2A6D52
Generated	2026-08-05

Product Overview

Control relay, 24 V DC, 12DI(4AI), 6DO relays, time, expandable

Easy700 programmable relay; 24 V DC; 12 ED(4EA), 6SR; No screen; With watch

Expandable electronic control relay, rated operating voltage 24VDC, 12 digital inputs 24VDC, 4 inputs can be used as analog inputs, 6 relay outputs, without keypad, without LCD display, time switch, easyLink, expandable with digital inputs and outputs, expandable to the bus systems AS-Interface / PROFIBUS-DP / CANopen / DeviceNet, custom labeling of control relay with inscription software Label editor delivery of the control relay with user program possible.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4519777Control relay, 24 V DC, 12DI(4AI), 6DO relays, time, expandableExpandable electronic control relay, rated operating voltage 24VDC, 12 digital inputs 24VDC, 4 inputs can be used as analog inputs, 6 relay outputs, without keypad, without LCD display, time switch, easyLink, expandable with digital inputs and outputs, expandable to the bus systems AS-Interface / PROFIBUS-DP / CANopen / DeviceNet, custom labeling of control relay with inscription software Labeleditor delivery of the control relay with user program possible.Delivery program
Basic functioneasy700 (expandable)DescriptionExpandable: Digital inputs/outputs, bus systems AS-Interface, PROFIBUS-DP, CANopen®, DeviceNet
customized laser inscription or delivery with user program possible with EASY-COMBINATION-* product (article No. 2010781)InputsDigital12of which can be used as analog4OutputsQuantity of outputsRelays: 6Outputs6 NumberAdditional featuresReal time clock?ExpansionsExpandableSupply voltage24 V DCSoftwareEASY-SOFT-BASIC/-PROConnection

typescrew terminalTechnical data

GeneralStandardsEN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27ApprovalsCSA

UL

EACWeight0.3 kgMountingTop-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1

(accessories)Terminal capacitiesSolid0.2/4 (AWG 22 - 12) mm²Flexible with ferrule0.2/2.5 (AWG 22 - 12) mm²Standard

screwdriver0.8 x 3.5 mmMax. tightening torque0.6 NmClimatic environmental conditionsOperating ambient temperat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY719-DC-RCX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.