

INDUSTRIAL COMPONENT DATA

EASY512-DC-RC 274109 0004519758 EATON ELECTRIC

Control relay, 24 V DC, 8DI(2AI), 4DO relays, display, time

Brand: EATON - MOELLER | Manufacturer Part Number: EASY512-DC-RC



Manufacturer	EATON - MOELLER
MPN / Reference	EASY512-DC-RC
Catalog number	0004519758
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-B0A86AAF6A
Generated	2026-08-03

Product Overview

Control relay, 24 V DC, 8DI(2AI), 4DO relays, display, time

Electronic control relay, rated operating voltage 24VDC, 8 digital inputs 24VDC, 2 inputs can be used as analog inputs, 4 relay outputs, keypad, LCD-display, time switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

Control relay, 24 V DC, 8DI(2AI), 4DO relays, display, time EL-Nummer (Norway) 0004519758 Electronic control relay, rated operating voltage 24VDC, 8 digital inputs 24VDC, 2 inputs can be used as analog inputs, 4 relay outputs, keypad, LCD-display, time switch [Delivery program

Basic function easy500 Description Stand alone

customized laser inscription or delivery with user program possible with EASY-COMBINATION-* product (article No.

2010781) Inputs Digital 8 of which can be used as analog 2 Outputs Outputs 4 Number Additional features Real time clock

? Display & keypad ? Supply voltage 24 V DC Software EASY-SOFT-BASIC/-PRO , Technical data

General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 Dimensions (W x H x D) 71.5 x 90 x 58 (4 PE) mm Weight 0.2 kg Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets

ZB4-101-GF1 (accessories) Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12)

mm² Standard screwdriver 3.5 x 0.8 mm Max. tightening torque 0.6 Nm Climatic environmental conditions Operating ambient temperature In accordance with IEC 60068-2-1, -25 - +55 °C Condensation Take appropriate measures to prevent condensation LCD display (clearly legible) 0 - 55 °C Storage [?] -40 - +70 °C relative humidity in accordance with IEC

60068-2-30, IEC 60068-2-78

5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY512-DC-RC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.