

INDUSTRIAL COMPONENT DATA

EASY512-DC-RCX 274110 0004519759 EATON ELECTRIC

Control relay, 24 V DC, 8DI(2AI), 4DO relays, time

Brand: EATON - MOELLER | Manufacturer Part Number: EASY512-DC-RCX



Manufacturer	EATON - MOELLER
MPN / Reference	EASY512-DC-RCX
Catalog number	0004519759
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-5B12B3B961
Generated	2026-08-04

Product Overview

Control relay, 24 V DC, 8DI(2AI), 4DO relays, time

Electronic control relay, rated operating voltage 24VDC, 8 digital inputs 24VDC, 2 inputs can be used as analog inputs, 4 relay outputs, without keypad, without LCD display, time switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4519759Control relay, 24 V DC, 8DI(2AI), 4DO relays, timeElectronic control relay, rated operating voltage 24VDC, 8 digital inputs 24VDC, 2 inputs can be used as analog inputs, 4 relay outputs, without keypad, without LCD display, time switchDelivery program

Basic functioneasy500DescriptionStand alone

customized laser inscription or delivery with user program possible with EASY-COMBINATION-* product (article No.

2010781)InputsDigital8of which can be used as analog2OutputsQuantity of outputsRelays: 4Outputs4 NumberAdditional

featuresReal time clock?Supply voltage24 V DCSoftwareEASY-SOFT-BASIC/-PROConnection typescrew

terminalTechnical data

GeneralStandardsEN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27ApprovalsCSA

UL

EACDimensions (W x H x D)71.5 x 90 x 58 (4 PE) mmWeight0.2 kgMountingTop-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)Terminal capacitiesSolid0.2/4 (AWG 22 - 12) mm2Flexible with ferrule0.2/2.5 (AWG 22 - 12) mm2Standard screwdriver0.8 x 3.5 mmMax. tightening torque0.6 NmClimatic environmental

conditions Operating ambient temperature In accordance with IEC 60068-2-1, -25 - +55 °C Condensation Take appropriate measures to prevent condensation Storage [?] -40 - +70 °C relative humidity in accordance with IEC 60068-2-30, IEC 60068-2-78
5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations In accordance with IEC 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY512-DC-RCX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.