

INDUSTRIAL COMPONENT DATA

EASY802-DC-SWD 152901 EATON ELECTRIC Control relay, 24 V DC, SmartWire-DT

Brand: EATON - MOELLER | Manufacturer Part Number: EASY802-DC-SWD



Manufacturer	EATON - MOELLER
MPN / Reference	EASY802-DC-SWD
Catalog number	152901
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-57EE893C7D
Generated	2026-08-04

Product Overview

Control relay, 24 V DC, SmartWire-DT

EASY800 programmable relay for SmartWire-DT communication. 24 V DC

Electronic control relay with SmartWire-DT, rated operating voltage 24VDC up to 99 SmartWire-DT modules with a total of up to 166 inputs/outputs can be connected via the SmartWire-DT line., serial interface for programming and for connection of a remote text display, touch panels or for connection to the Ethernet gateway EASY209-SE, real-time clock delivery of the control relay with user program possible.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

EL-Nummer (Norway)4520980Control relay, 24 V DC, SmartWire-DTElectronic control relay with SmartWire-DT, rated operating voltage 24VDC up to 99 SmartWire-DT modules with a total of up to 166 inputs/outputs can be connected via the SmartWire-DT line., serial interface for programming and for connection of a remote text display, touch panels or for connection to the Ethernet gateway EASY209-SE, real-time clock delivery of the control relay with user program possible.Delivery program

Product rangeSmartWire-DT coordinatorsBasic functioneasy800 with SmartWire-DTDescriptionCombines the functionality of an easy800 with direct connection to SmartWire-DT communication system

Up to 99 SmartWire-DT modules with a total of up to 166 digital inputs/outputs and/or up to 128 analog inputs/outputs can be connected via a SmartWire-DT lineInputsSmartWire-DT83OutputsSmartWire-DT83Additional featuresReal time clock?ExpansionsSmartWire-DTSupply voltage24 V DCSoftwareEASY-SOFT-PROConnection typescrew

terminalNotesDepending on the hardware, such as high-speed counter, PWM output, integrated analog input/output are not supported

Technical data

GeneralStandardsEN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27ApprovalsCSA
UL

EACDimensions (W x H x D)35 x 110 x 125.5 (2 PE) mmWeight0.16 kgMountingTop-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)Terminal capacitiesSolid0.2/1.5 (AWG 24 - 16) mm²Flexible with ferrule0.2/1.5 (AWG 24 - 16) mm²C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY802-DC-SWD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.