

INDUSTRIAL COMPONENT DATA

EASY719-AB-RC 274113 0004519770 EATON ELECTRIC

Control relay, 24VAC, 12DI(4AI), 6DO relays, display, time, e..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY719-AB-RC



Manufacturer	EATON - MOELLER
MPN / Reference	EASY719-AB-RC
Catalog number	0004519770
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-45A0D02055
Generated	2026-08-05

Product Overview

Control relay, 24VAC, 12DI(4AI), 6DO relays, display, time, expandable

Easy700 programmable relay; 24 V AC; 12 ED(4EA), 6SR; With screen; With watch

Expandable electronic control relay, rated operating voltage 24VAC, 12 digital inputs 24VDC, 4 inputs can be used as analog inputs, 6 relay outputs, keypad, LCD-display, time switch, easyLink, expandable with digital inputs and outputs, expandable to the bus systems AS-Interface, PROFIBUS-DP, integrated, deviceNet, custom labeling of control relay with inscription software Label editor delivery of the control relay with user program possible.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4519770Control relay, 24VAC, 12DI(4AI), 6DO relays, display, time, expandableExpandable electronic control relay, rated operating voltage 24VAC, 12 digital inputs 24VDC, 4 inputs can be used as analog inputs, 6 relay outputs, keypad, LCD-display, time switch, easyLink, expandable with digital inputs and outputs, expandable to the bus systems AS-Interface, PROFIBUS-DP, integrated, deviceNet, custom labeling of control relay with inscription software Label editor delivery of the control relay with user program possible.Delivery program Basic functioneasy700 (expandable)DescriptionExpandable: Digital inputs/outputs, bus systems AS-Interface, PROFIBUS-DP, CANopen®, DeviceNet customized laser inscription or delivery with user program possible with EASY-COMBINATION-* product (article No. 2010781)InputsDigital12of which can be used as analog4OutputsQuantity of outputsRelays: 6Outputs6 NumberAdditional featuresReal time clock?Display & keypad?ExpansionsExpandableSupply voltage24 V

ACS Software EASY-SOFT-BASIC/-PRO Connection type screw terminal Technical data

General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 Approvals CSA

UL

EAC Weight 0.3 kg Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1

(accessories) Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm² Standard

screwdriver 0.8 x 3.5 mm Max. tightening torque 0.6 Nm Climatic environmental conditions Operating ambient....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY719-AB-RC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.