

INDUSTRIAL COMPONENT DATA

EASY512-AB-RCX 274102 0004519751 EATON ELECTRIC

Control relay, 24VAC, 8DI(2AI), 4DO relays, time

Brand: EATON - MOELLER | Manufacturer Part Number: EASY512-AB-RCX



Manufacturer	EATON - MOELLER
MPN / Reference	EASY512-AB-RCX
Catalog number	0004519751
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-9A0B42A122
Generated	2026-08-04

Product Overview

Control relay, 24VAC, 8DI(2AI), 4DO relays, time

Electronic control relay, rated operating voltage 24VAC, 8 digital inputs 24VDC, M69, without keypad, without LCD display, time switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4519751Control relay, 24VAC, 8DI(2AI), 4DO relays, timeElectronic control relay, rated operating voltage 24VAC, 8 digital inputs 24VDC, M69, without keypad, without LCD display, time switchDelivery program Basic functioneasy500DescriptionStand alone customized laser inscription or delivery with user program possible with EASY-COMBINATION-* product (article No. 2010781)InputsDigital8of which can be used as analog2OutputsQuantity of outputsRelays: 4Outputs4 NumberAdditional featuresReal time clock?Supply voltage24 V ACSoftwareEASY-SOFT-BASIC/-PROConnection typescrew terminalTechnical data GeneralStandardsEN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27ApprovalsCSA UL EACDimensions (W x H x D)71.5 x 90 x 58 (4 PE) mmWeight0.2 kgMountingTop-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)Terminal capacitiesSolid0.2/4 (AWG 22 - 12) mmFlexible with ferrule0.2/2.5 (AWG 22 - 12) mmStandard screwdriver0.8 x 3.5 mmMax. tightening torque0.6 NmClimatic environmental conditionsOperating ambient temperatureIn accordance with IEC 60068-2-1, -25 - +55 °CCondensationTake appropriate

measures to prevent condensationStorage [?]-40 - +70 °Crelative humidityin accordance with IEC 60068-2-30, IEC 60068-2-78

5 - 95 %Air pressure (operation)795 - 1080 hPaAmbient conditions, mechanicalProtection type (IEC/EN 60529, EN50178, VBG 4)IP20VibrationsIn accordance with IEC 60068-2-6

constant amplitude 0.15 mm: 10 - 57

constant...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY512-AB-RCX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.