

**INDUSTRIAL COMPONENT DATA**

# T0-1-15411/IVS 009270 Y7-9270 EATON ELECTRIC ON-OFF switches, Contacts: 1, 20 A, front plate: STOP-START, 45..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15411/IVS



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-1-15411/IVS  |
| Catalog number  | Y7-9270         |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-5EC62553F5   |
| Generated       | 2026-08-06      |

## Product Overview

ON-OFF switches, Contacts: 1, 20 A, front plate: STOP-START, 45 °, maintained, service distribution board mounting

ON-OFF disconnecter switch 1 pole 20 A Indicator plate:

Eaton Moeller® series T0 ON-OFF switches, T0, 20 A, service distribution board mounting, 1 contact unit(s), Contacts: 1, 45 °, maintained, Without 0 (Off) position, STOP-START, Design number 15411

On-Off switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 1, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 1 contact unit(s), Rated uninterrupted current: I<sub>u</sub>= 20 A, front plate: STOP-START

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

## Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On-off switch Catalog Number 009270 Model Code T0-1-15411/IVS EAN 4015080092704 Product Length/Depth 82 mm Product Height 55 mm Product Width 54 mm Product Weight 0.106 kg

Certifications IEC/EN 60204

CE

CSA File No.: 012528

UL

UL Category Control No.: NLRV

UL 60947-4-1

CSA

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

VDE 0660

UL File No.: E36332

IEC/EN 60947

CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 009270 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

2

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

4

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-15411/IVS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.