

INDUSTRIAL COMPONENT DATA

T0-3-15391/IVS 036484 Y7-36484 EATON ELECTRIC Universal control switches,Contacts 6,Stay-put switches with 3..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15391/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15391/IVS
Catalog number	Y7-36484
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-C7273A2FD6
Generated	2026-08-05

Product Overview

Universal control switches,Contacts 6,Stay-put switches with 3 positions,20A,front plate: 2-0-1, 45 °, maintained, service distribution board mount.

Universal control switch: 6 poles, 3 interlocking positions, 20 A

Universal control switches, T0, 20 A, service distribution board mounting, 3 contact unit(s), Contacts: 6, Stay-put switches with 3 positions, 45 °, maintained, 2-0-1, Design number 15391

Universal control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Spring-return: Stay-put switches with 3 positions, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 1 contact closed in each position, Additionally 1 contact closed in position 0 and 1, Additionally 1 contact closed in position 0 and 2, Additionally 1 contact closed in position 0 and 3 , 3 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Universal control switch Catalog Number 036484 Model Code T0-3-15391/IVS
EAN 4015080364849 Product Length/Depth 101 mm Product Height 55 mm Product Width 54 mm Product Weight 0.155 kg
Certifications IEC/EN 60947
UL 60947-4-1

CSA

UL File No.: E36332

VDE 0660

CSA-C22.2 No. 94

CE

CSA Class No.: 3211-05

UL

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

CSA File No.: 012528

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{scw}) for a time of 1 second

ETIM for 036484 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Group switch

Number of poles (EF001391)

3

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15391/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.