

INDUSTRIAL COMPONENT DATA

T0-3-15391/I1 207112 Y7-207112 EATON ELECTRIC Universal control switches, Contacts: 6, Stay-put switches wit..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15391/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15391/I1
Catalog number	Y7-207112
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-2D411C79E4
Generated	2026-08-06

Product Overview

Universal control switches, Contacts: 6, Stay-put switches with 3 positions, 20 A, front plate: 2-0-1, 45 °, maintained, surface mounting

T0-3-15391/I1

Eaton Moeller® series T0 Universal control switches, T0, 20 A, surface mounting, 3 contact unit(s), Contacts: 6, Stay-put switches with 3 positions, 45 °, maintained, 2-0-1, Design number 15391

Universal control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Spring-return: Stay-put switches with 3 positions, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 1 contact closed in each position, Additionally 1 contact closed in position 0 and 1, Additionally 1 contact closed in position 0 and 2, Additionally 1 contact closed in position 0 and 3, 3 contact unit(s) , Rated uninterrupted current: Iu= 20 A, front plate: 2-0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Universal control switch Catalog Number 207112 Model Code T0-3-15391/I1 EAN 4015082071127 Product Length/Depth 137 mm Product Height 122 mm Product Width 80 mm Product Weight 0.288 kg Certifications IEC/EN 60947 VDE 0660

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 207112 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Group switch

Number of poles (EF001391)

0

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Surface mounted device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15391/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.