

INDUSTRIAL COMPONENT DATA

T0-1-15521/EZ 064962 Y7-64962 EATON ELECTRIC On-Off switch, 1 pole, 20 A, 90 °, centre mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15521/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-15521/EZ
Catalog number	Y7-64962
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E4549F6B32
Generated	2026-08-02

Product Overview

On-Off switch, 1 pole, 20 A, 90 °, centre mounting

ON-OFF Disconnect Switch 1 Pole 20 A 90° Flush Mount with

Eaton Moeller® series T0 On-Off switch, 1 pole, 20 A, 90 °, center mounting T0-1-15521/EZ

On-Off switch, Product range: On-Off switch, Part group reference: T0, with black thumb grip and front plate, 1 pole, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 90 °, Switching performance: maintained/momentary, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On-off switch Catalog Number 064962 Model Code T0-1-15521/EZ EAN 4015080649625 Product Length/Depth 96 mm Product Height 48 mm Product Width 48 mm Product Weight 0.101 kg

Certifications CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

CSA Class No.: 3211-05

IEC/EN 60204

CSA File No.: 012528

CE

CSA
IEC/EN 60947-3
VDE 0660
IEC/EN 60947
CSA-C22.2 No. 94
UL Category Control No.: NLRV
UL File No.: E36332
UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 064962 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
20 A
Rated permanent current at AC-21, 400 V (EF009165)
20 A
Rated operation power at AC-3, 400 V (EF001364)
5.5 kW
Rated short-time withstand current I_{cw} (EF007050)
0.32 kA
Rated operation power at AC-23, 400 V (EF007027)
5.5 kW
Switching power at 400 V (EF009166)
5.5 kW
Conditioned rated short-circuit current I_q (EF001444)
6 kA
Number of poles (EF001391)
1
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-15521/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.