

INDUSTRIAL COMPONENT DATA

T0-1-15541/E 098862 Y7-98862 EATON ELECTRIC Changeoverswitches, Contacts: 2, 20 A, front plate: USV-NETZ, 90..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15541/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-15541/E
Catalog number	Y7-98862
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-5FDA14C2FC
Generated	2026-08-04

Product Overview

Changeoverswitches, Contacts: 2, 20 A, front plate: USV-NETZ, 90 °, maintained, flush mounting

Switch Switch 2 poles 20 A Indicator Plate: USV-NETZ 90°

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, flush mounting, 1 contact unit(s), Contacts: 2, 90 °, maintained, Without 0 (Off) position, USV-NETZ, Design number 15541

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: USV-NETZ, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 098862 Model Code T0-1-15541/E EAN 4015080988625 Product Length/Depth 76 mm Product Height 8 mm Product Width 48 mm Product Weight 0.083 kg

Certifications CSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

CSA File No.: 012528

CSA-C22.2 No. 94

VDE 0660

IEC/EN 60947

CE

UL Category Control No.: NLRV

UL 60947-4-1

IEC/EN 60947-3

UL

CSA Class No.: 3211-05

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 098862 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

1

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF001...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-15541/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.