

INDUSTRIAL COMPONENT DATA

T0-2-15512/I1 207093 Y7-207093 EATON ELECTRIC ON-OFF button, Contacts: 4, Spring-return in START position, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15512/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15512/I1
Catalog number	Y7-207093
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-E1C418BA0D
Generated	2026-08-05

Product Overview

ON-OFF button, Contacts: 4, Spring-return in START position, 20 A, front plate: 0-1

T0-2-15512/I1

Eaton Moeller® series T0 ON-OFF button, T0, 20 A, surface mounting, 2 contact unit(s), Contacts: 4, Spring-return in START position, 90 °, maintained, With 0 (Off) position, With spring-return to 1, 0-1

ON OFF button, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate,

Contacts: 4, Spring-return: Spring-return in START position, Degree of Protection: IP65, Design: surface mounting,

Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 1, 2 contact unit(s),

Rated uninterrupted current: I_u= 20 A, front plate: 0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Accessory ON OFF button Catalog Number 207093 Model Code T0-2-15512/I1

EAN 4015082070939 Product Length/Depth 137 mm Product Height 102 mm Product Width 80 mm Product Weight 0.264

kg Certifications IEC/EN 60947-3

IEC/EN 60947

VDE 0660

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 207093 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Surface mounted device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15512/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.