

INDUSTRIAL COMPONENT DATA

T0-2-15512/IVS 041232 Y7-41232 EATON ELECTRIC ON-OFF button, Contacts: 4, Spring-return in START position, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15512/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15512/IVS
Catalog number	Y7-41232
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-FB3C331DDC
Generated	2026-08-02

Product Overview

ON-OFF button, Contacts: 4, Spring-return in START position, 20 A, front plate: 0-1

ON-OFF pushbutton switch 4-pole 20 A Indicator plate: 0-1

Eaton Moeller® series T0 ON-OFF button, T0, 20 A, service distribution board mounting, 2 contact unit(s), Contacts: 4, Spring-return in START position, 90 °, maintained, 0-1

ON OFF button, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Spring-return: Spring-return in START position, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 1, 2 contact unit(s), Rated uninterrupted current: I_u = 20 A, front plate: 0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Accessory ON OFF button Catalog Number 041232 Model Code T0-2-15512/IVS
EAN 4015080412328 Product Length/Depth 92 mm Product Height 55 mm Product Width 54 mm Product Weight 0.12 kg

Certifications CSA File No.: 012528

CSA

IEC/EN 60947

UL Category Control No.: NLRV

CSA Class No.: 3211-05

IEC/EN 60947-3

CSA-C22.2 No. 94

CE

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

VDE 0660

UL File No.: E36332

UL 60947-4-1

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 041232 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

4

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15512/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.