

INDUSTRIAL COMPONENT DATA

T0-2-8182/E 011700 Y7-11700 EATON ELECTRIC Spring-return switch, Contacts: 4, 20 A, front plate: START 1-0-2..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8182/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8182/E
Catalog number	Y7-11700
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-71EF94B99F
Generated	2026-08-04

Product Overview

Spring-return switch, Contacts: 4, 20 A, front plate: START>1-0-2

Switch with return; 4 poles; 20 A; Indicator plate:

Eaton Moeller® series T0 Spring-return switch, T0, 20 A, flush mounting, 2 contact unit(s), Contacts: 4, 45 °, momentary/maintained, With 0 (Off) position, with spring-return from both directions, START>1-0-2

Spring-return switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, with spring-return from both directions, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: START>1-0-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Spring-return switch Catalog Number 011700 Model Code T0-2-8182/E EAN 4015080117001 Product Length/Depth 86 mm Product Height 48 mm Product Width 48 mm Product Weight 0.108 kg

Certifications CSA File No.: 012528

IEC/EN 60947

UL File No.: E36332

CSA Class No.: 3211-05

CSA-C22.2 No. 94

UL 60947-4-1

IEC/EN 60204

CSA

CSA-C22.2 No. 60947-4-1-14

UL

CE

UL Category Control No.: NLRV

VDE 0660

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 011700 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

4

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8182/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.