

INDUSTRIAL COMPONENT DATA

T0-3-15391/E 029365 Y7-29365 EATON ELECTRIC Universal control switches, Contacts: 6, Stay-put switches with ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15391/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15391/E
Catalog number	Y7-29365
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-989644B89B
Generated	2026-08-02

Product Overview

Universal control switches, Contacts: 6, Stay-put switches with 3 positions, 20 A, front plate: 2-0-1, 45 °, maintained, flush mounting

Universal control switch: 6 poles, 3 interlocking positions, 20 A

Eaton Moeller® series T0 Universal control switches, T0, 20 A, flush mounting, 3 contact unit(s), Contacts: 6, Stay-put switches with 3 positions, 45 °, maintained, 2-0-1, Design number 15391

Universal control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Spring-return: Stay-put switches with 3 positions, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 1 contact closed in each position, Additionally 1 contact closed in position 0 and 1, Additionally 1 contact closed in position 0 and 2, Additionally 1 contact closed in position 0 and 3, 3 contact unit(s) , Rated uninterrupted current: I_u= 20 A, front plate: 2-0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Universal control switch Catalog Number 029365 Model Code T0-3-15391/E EAN 4015080293651 Product Length/Depth 95 mm Product Height 48 mm Product Width 48 mm Product Weight 0.127 kg

Certifications IEC/EN 60204

UL

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

UL 60947-4-1

IEC/EN 60947

CSA File No.: 012528

CSA-C22.2 No. 94

UL File No.: E36332

IEC/EN 60947-3

CSA

UL Category Control No.: NLRV

CE

VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 029365 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Group switch

Number of poles (EF001391)

3

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15391/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.