

INDUSTRIAL COMPONENT DATA

T0-3-15513/EZ 050724 Y7-50724 EATON ELECTRIC ON-OFF button, Contacts: 6, Spring-return in START position, 20..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15513/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15513/EZ
Catalog number	Y7-50724
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-7B630D2CF3
Generated	2026-08-05

Product Overview

ON-OFF button, Contacts: 6, Spring-return in START position, 20 A, front plate: 0-1

ON-OFF pushbutton switch 6-pole 20 A Indicator plate: 0-1

Eaton Moeller® series T0 ON-OFF button, T0, 20 A, center mounting, 3 contact unit(s), Contacts: 6, Spring-return in START position, 90 °, maintained, With 0 (Off) position, With spring-return to 1, 0-1

ON OFF button, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Spring-return: Spring-return in START position, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 1, 3 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Accessory ON OFF button Catalog Number 050724 Model Code T0-3-15513/EZ

EAN 4015080507246 Product Length/Depth 115 mm Product Height 48 mm Product Width 48 mm Product Weight 0.153 kg

Certifications IEC/EN 60947

CSA

UL

CSA File No.: 012528

UL 60947-4-1

UL File No.: E36332

IEC/EN 60947-3

CE

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

VDE 0660

CSA Class No.: 3211-05

CSA-C22.2 No. 94

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{scw}) for a time of 1 second

ETIM for 050724 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15513/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.