

## INDUSTRIAL COMPONENT DATA

**STN1,0(400/230) 204992 Y7-204992 EATON ELECTRIC Control transformer, 1.0kVA, 1p, primary 400V, secondary 230V**

Brand: EATON - MOELLER | Manufacturer Part Number: STN1,0(400/230)



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | STN1,0(400/230)               |
| Catalog number  | Y7-204992                     |
| Category        | One-phase control transformer |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-277DEFFABF                 |
| Generated       | 2026-08-06                    |

**Product Overview**

Control transformer, 1.0kVA, 1p, primary 400V, secondary 230V

STN1,0(400/230)

Eaton Moeller® series STN Control transformer, 1 kVA, Rated input voltage  $400 \pm 5\%$  V, Rated output voltage 230 V  
Control transformer, Product range: Single-phase control transformers ST..., Basic function: Single-phase STN control transformers, Rated input voltage:  $400 \pm 5\%$  V, Rated output voltage: 230 V, Rated power: 1 kVA, Short-time rating: 3.28 kVA, Degree of Protection: IP00, Standards Built and tested to: IEC/EN 61558-2-2, VDE 0570 Part 2-2, Suitable for use to: IEC/EN 60204-1, ÖVE-EN 13, VDE 0113, VDE 0100 Part 410

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Transformers

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series STN Control transformer Catalog Number 204992 Model Code STN1,0(400/230) EAN 4015082049928 Product Length/Depth 150 mm Product Height 145 mm Product Width 151 mm Product Weight 9.6 kg

Certifications Certified by UL for use in Canada

UL Recognized

CSA-C22.2 No. 66

CSA-C22.2 No. 66.1-06

VDE 0113, VDE 0100 Part 410

IEC/EN 61558-2-2

UL File No.: E167225

CE

UL report applies to both US and Canada

IEC/EN 60204-1, ÖVE-EN 13

CSA-C22.2 No. 66.2-06

VDE 0570 Part 2-2

UL 506

UL5085-1

UL 5085-2

UL Category Control No.: XPTQ2, XPTQ8 Catalog Notes Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C Features & Functions

Features Separate windings

Fully Vacuum-impregnated General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Connection lug Yes for > 115 A

Connection type Terminations, < 115 A Duty factor 100 % Insulation class B Primary tapping  $\pm 5$  % Product category

Single-phase control transformers ST Suitable for Branch circuits, (UL/CSA) Type Single-phase STN control transformers

Electrical rating

Efficiency 94 % No-load losses 33 W Rated frequency - min 50 Hz Rated frequency - max 60 Hz Rated power 1 VA

Relative short-circuit voltage 2.2 % Short-circuit losses 26 W Short-time rating 3.28 kVA Voltage rating - max 600 V Design verification

Equipment heat dissipation, current-d...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / STN1,0(400/230) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.