

INDUSTRIAL COMPONENT DATA

STZ13,3(*/*) 201064 Y7-201064 EATON ELECTRIC Control transformer, 13.3 kVA, Rated input voltage 50 - 950 ± 5..

Brand: EATON - MOELLER | Manufacturer Part Number: STZ13,3(*/*)



Manufacturer	EATON - MOELLER
MPN / Reference	STZ13,3(*/*)
Catalog number	Y7-201064
Category	One-phase control transformer
Minimum order	1 Pcs
Document ID	EO-A7BFF77035
Generated	2026-08-04

Product Overview

Control transformer, 13.3 kVA, Rated input voltage 50 - 950 ± 5 % V, Rated output voltage 12 - 1000 V

STZ13,3(*/*)

Eaton Moeller® series STZ Control transformer, 13.3 kVA, Rated input voltage 50 - 950 ± 5 % V, Rated output voltage 12 - 1000 V

Control transformer, Product range: Single-phase control transformers ST..., Basic function: Single-phase control, isolating and safety transformers STI, STZ, Rated input voltage: 50 - 950 ± 5 % V, Rated output voltage: 12 - 1000 V, Rated power: 13.3 kVA, Short-time rating: 34 kVA, Degree of Protection: IP00, Standards Built and tested to: IEC/EN 61558-2-2/2-4/2-6, VDE 0570 Part 2-2, VDE 0570 Part 2-6 (safety transformers), VDE 0570 Part 2-4 (isolating transformer), Suitable for use to: IEC/EN 60204-1, ÖVE-EN 13, VDE 0113, VDE 0100 Part 410

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Transformers**

Additional Product Information

General specifications

Product Name Eaton Moeller® series STZ Control transformer Catalog Number 201064 Model Code STZ13,3(*/*) Product Length/Depth 270 mm Product Height 440 mm Product Width 320 mm Product Weight 80 kg Certifications VDE 0570 Part 2-4 (isolating transformer)

IEC/EN 61558-2-2

IEC/EN 61558-2-2/2-4/2-6

CE

IEC/EN 60204-1, ÖVE-EN 13

VDE 0113, VDE 0100 Part 410

UL Category Control No.: XPTQ2, XPTQ8

VDE 0570 Part 2-6 (safety transformers)

VDE 0570 Part 2-2 Catalog Notes Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C Features & Functions

Features Separate windings

Fully Vacuum-impregnated

Reinforced insulation General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Connection lug Yes for < 63 A

Connection type Terminations, < 63 A Duty factor 100 % Insulation class B Primary tapping ± 5 % Product category

Single-phase control transformers ST Suitable for Branch circuits, (UL/CSA) Type Single-phase control, isolating and safety transformer Electrical rating

Efficiency 97 % No-load losses 95 W Rated frequency - min 50 Hz Rated frequency - max 60 Hz Rated power 13.3 VA

Relative short-circuit voltage 3.5 % Short-circuit losses 265 W Short-time rating 34 kVA Voltage rating - max 600 V Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / STZ13,3(*) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.