

INDUSTRIAL COMPONENT DATA

STZ8,3(*/*) 201062 Y7-201062 EATON ELECTRIC Control transformer, 8.3 kVA, Rated input voltage 50 - 950 ± 5 %..

Brand: EATON - MOELLER | Manufacturer Part Number: STZ8,3(*/*)



Manufacturer	EATON - MOELLER
MPN / Reference	STZ8,3(*/*)
Catalog number	Y7-201062
Category	One-phase control transformer
Minimum order	1 Pcs
Document ID	EO-3EFEB814F7
Generated	2026-08-04

Product Overview

Control transformer, 8.3 kVA, Rated input voltage 50 - 950 ± 5 % V, Rated output voltage 12 - 1000 V

STZ8,3(*/*)

Eaton Moeller® series STZ Control transformer, 8.3 kVA, Rated input voltage 50 - 950 ± 5 % V, Rated output voltage 12 - 1000 V

Control transformer, Product range: Single-phase control transformers ST..., Basic function: Single-phase control, isolating and safety transformers STI, STZ, Rated input voltage: 50 - 950 ± 5 % V, Rated output voltage: 12 - 1000 V, Rated power: 8.3 kVA, Short-time rating: 21 kVA, Degree of Protection: IP00, Standards Built and tested to: IEC/EN 61558-2-2/2-4/2-6, VDE 0570 Part 2-2, VDE 0570 Part 2-6 (safety transformers), VDE 0570 Part 2-4 (isolating transformer), Suitable for use to: IEC/EN 60204-1, ÖVE-EN 13, VDE 0113, VDE 0100 Part 410

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Transformers
--------------	--------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series STZ Control transformer Catalog Number 201062 Model Code STZ8,3(*/*) Product Length/Depth 244 mm Product Height 374 mm Product Width 260 mm Product Weight 55 kg Certifications VDE 0570 Part 2-2

CE

VDE 0570 Part 2-6 (safety transformers)

IEC/EN 60204-1, ÖVE-EN 13

IEC/EN 61558-2-2

VDE 0113, VDE 0100 Part 410

UL Category Control No.: XPTQ2, XPTQ8

IEC/EN 61558-2-2/2-4/2-6

VDE 0570 Part 2-4 (isolating transformer) Catalog Notes Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C Product specifications

Type Single-phase control, isolating and safety transformer Features Separate windings

Fully Vacuum-impregnated

Reinforced insulation 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product stan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / STZ8,3(*) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.