

INDUSTRIAL COMPONENT DATA

CU12X5 034121 Y7-34121 EATON ELECTRIC Copper busbar, 12x5x1500mm, tinned

Brand: EATON - MOELLER | Manufacturer Part Number: CU12X5



Manufacturer	EATON - MOELLER
MPN / Reference	CU12X5
Catalog number	Y7-34121
Category	Busbar
Minimum order	10 Pcs
Document ID	EO-DDF1C664E7
Generated	2026-08-06

Product Overview

Copper busbar, 12x5x1500mm, tinned

Copper distributor, 12x5x1500mm, tin-plated

Flat copper bar for CI distribution system, tin-plated surface, 12x5 mm, supplied in lengths=1500mm, le=160A, CI distribution board up to 160A=1x 12x5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Connection Accessories for Enclosures
--------------	---

Additional Product Information

Copper busbar, 12x5x1500mm, tinnedFlat copper bar for CI distribution system, tin-plated surface, 12x5 mm, supplied in lengths=1500mm, le=160A, CI distribution board up to 160A=1x 12x5

General specificationsProduct nameEaton xEffect SASY 60i copper busbar flatPart

no.CU12X5EAN4015080341215Product Length/Depth1500 millimetreProduct height5 millimetreProduct width12

millimetreProduct weight0.81 kilogramCompliancesRoHS conformCertificationsEN 13061Product TradenamexEffect SASY

60iProduct TypeCopper busbarProduct Sub TypeFlatDelivery programType60 mm system

Accessory panel building

Compact system

General switchboard accessory

Modular busbar system

System for flat busbarsModelFlatAccessory/spare part typeFlat copper barsNominal current160 ATechnical Data -

ElectricalUninterrupted current (Iu) of bar450 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)

200 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

320 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

630 A (30 x 10 mm, Tu=35 °C and Ts=65 °C)

360 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)

520 A (20 x 10 mm, Tu=35 °C and Ts=65 °C) Rated operation current (Ie) 160 A Technical Data - Mechanical Unit

type Modular system Surface finishing Tinned Surface protection Tinned Material Copper, tinned Distance between busbar

centers 60 mm Additional information Functions Flat busbar

System for flat busbars

Prepared enclosure Special features Flat copper busbars Used with SH0165/2

60 mm system

System for flat busbars

General switchboard accessory

Compact system

Accessory panel building

Modular busba...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU12X5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.