

INDUSTRIAL COMPONENT DATA

CU12X5-2250 005093 Y7-5093 EATON ELECTRIC Copper busbar, 12x5x2250mm, tinned

Brand: EATON - MOELLER | Manufacturer Part Number: CU12X5-2250



Manufacturer	EATON - MOELLER
MPN / Reference	CU12X5-2250
Catalog number	Y7-5093
Category	Busbar
Minimum order	10 Pcs
Document ID	EO-D2A8189C58
Generated	2026-08-05

Product Overview

Copper busbar, 12x5x2250mm, tinned

Copper distributor, 12x5x2250mm, tin-plated

Flat copper bar for CI distribution system, tin-plated surface, 12x5 mm, supplied in length=2250mm, Ie=160A, CI distribution board up to 160A=1x 12x5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Connection Accessories for Enclosures
--------------	---

Additional Product Information

Copper busbar, 12x5x2250mm, tinnedFlat copper bar for CI distribution system, tin-plated surface, 12x5 mm, supplied in length=2250mm, Ie=160A, CI distribution board up to 160A=1x 12x5

General specificationsProduct nameEaton xEffect SASY 60i copper busbar flatPart

no.CU12X5-2250EAN4015080050933Product Length/Depth2250 millimetreProduct height5 millimetreProduct width12 millimetreProduct weight1.21 kilogramCompliancesRoHS conformCertificationsEN 13061Product TradenamexEffect SASY 60iProduct TypeCopper busbarProduct Sub TypeFlatDelivery programType60 mm system

Accessory panel building

Compact system

General switchboard accessory

Modular busbar system

System for flat busbarsModelFlatAccessory/spare part typeFlat copper barsNominal current160 ATechnical Data - ElectricalUninterrupted current (Iu) of bar520 A (20 x 10 mm, Tu=35 °C and Ts=65 °C)

320 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

360 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)

450 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)

200 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

630 A (30 x 10 mm, Tu=35 °C and Ts=65 °C) Rated operation current (Ie) 160 A Technical Data - Mechanical Unit

type Modular system Surface finishing Tinned Surface protection Tinned Material Copper, tinned Distance between busbar centers 60 mm Additional information Functions Prepared enclosure

Flat busbar

System for flat busbars Special features Flat copper busbars Used with SH0165/2

Compact system

60 mm system

Modular busbar system

Accessory panel building

General switchboard accessory

System for....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU12X5-2250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.