

INDUSTRIAL COMPONENT DATA

CU20X10-2250 009839 Y7-9839 EATON ELECTRIC Copper busbar, 20x10x2250mm, tinned

Brand: EATON - MOELLER | Manufacturer Part Number: CU20X10-2250



Manufacturer	EATON - MOELLER
MPN / Reference	CU20X10-2250
Catalog number	Y7-9839
Category	Busbar
Minimum order	5 Pcs
Document ID	EO-BC24F99C98
Generated	2026-08-05

Product Overview

Copper busbar, 20x10x2250mm, tinned

Copper distributor, 20x10x2250mm, tin-plated

Flat copper bar for CI distribution system, tin-plated surface, 20x10 mm, supplied in lengths=2250mm, Ie=400A, CI distribution board up to 630A=1x 20x10+1x 20x5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Connection Accessories for Enclosures
--------------	---

Additional Product Information

Copper busbar, 20x10x2250mm, tinnedFlat copper bar for CI distribution system, tin-plated surface, 20x10 mm, supplied in lengths=2250mm, Ie=400A, CI distribution board up to 630A=1x 20x10+1x 20x5

General specificationsProduct nameEaton xEffect SASY 60i copper busbar flatPart

no.CU20X10-2250EAN4015080098393Product Length/Depth2250 millimetreProduct height10 millimetreProduct width20 millimetreProduct weight4.01 kilogramCompliancesRoHS conformCertificationsUL Listed

EN 13061Product TradenamexEffect SASY 60iProduct TypeCopper busbarProduct Sub TypeFlatDelivery programTypeAccessory panel building

General switchboard accessory

Modular busbar system for flat busbars

60 mm systemModelFlatAccessory/spare part typeFlat copper barsNominal current400 ATechnical Data -

ElectricalUninterrupted current (Iu) of bar200 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

360 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)

520 A (20 x 10 mm, Tu=35 °C and Ts=65 °C)

320 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

450 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)

630 A (30 x 10 mm, Tu=35 °C and Ts=65 °C) Rated operation current (Ie) 460 A Technical Data - Mechanical Unit

type Modular system Surface finishing Tinned Surface protection Tinned Material Copper, tinned Distance between busbar centers 60 mm Design verification as per IEC/EN 61439 - technical data Ambient operating temperature - max 35 °C Additional information Functions Prepared enclosure

System for flat busbars

Flat busbar Special features Flat copper busbars Used with SH0635/4

SH0632

Modular bus...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU20X10-2250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.