

## INDUSTRIAL COMPONENT DATA

# CU20X5-2250 007466 Y7-7466 EATON ELECTRIC Copper busbar, 20x5x2250mm, tinned

Brand: EATON - MOELLER | Manufacturer Part Number: CU20X5-2250



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | CU20X5-2250     |
| Catalog number  | Y7-7466         |
| Category        | Busbar          |
| Minimum order   | 10 Pcs          |
| Document ID     | EO-5B44700DEA   |
| Generated       | 2026-08-06      |

## Product Overview

Copper busbar, 20x5x2250mm, tinned

Copper distributor, 20x5x2250mm, tinned

Flat copper bar for CI distribution system, tin-plated surface, 20x5 mm, supplied in lengths=2250mm, Ie=250A, CI distribution board up to 630A=1x 20x5+1x 20x10

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                         |
|--------------|---------------------------------------------------------|
| Catalog path | EATON - MOELLER > Connection Accessories for Enclosures |
|--------------|---------------------------------------------------------|

## Additional Product Information

Copper busbar, 20x5x2250mm, tinnedFlat copper bar for CI distribution system, tin-plated surface, 20x5 mm, supplied in lengths=2250mm, Ie=250A, CI distribution board up to 630A=1x 20x5+1x 20x10

General specificationsProduct nameEaton xEffect SASY 60i copper busbar flatPart

no.CU20X5-2250EAN4015080074663Product Length/Depth2250 millimetreProduct height5 millimetreProduct width20 millimetreProduct weight2.01 kilogramCompliancesRoHS conformCertificationsUL Listed

EN 13061Product TradenamexEffect SASY 60iProduct TypeCopper busbarProduct Sub TypeFlatDelivery programType60 mm system

Accessory panel building

General switchboard accessory

Modular busbar system

System for flat busbarsModelFlatAccessory/spare part typeFlat copper barsNominal current250 ATechnical Data - ElectricalUninterrupted current (Iu) of bar630 A (30 x 10 mm, Tu=35 °C and Ts=65 °C)

200 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)  
520 A (20 x 10 mm, Tu=35 °C and Ts=65 °C)  
320 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)  
360 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)  
450 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)Rated operation current (Ie)250 ATechnical Data - MechanicalUnit typeModular  
systemSurface finishingTinnedSurface protectionTinnedMaterialCopper, tinnedDistance between busbar centers60  
mmDesign verification as per IEC/EN 61439 - technical dataAmbient operating temperature - max35 °CAdditional  
informationFunctionsFlat busbar  
Prepared enclosure  
System for flat busbarsSpecial featuresFlat copper busbarsUsed withSH0632  
SH0635/4  
System f...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU20X5-2250 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.