

INDUSTRIAL COMPONENT DATA

CU30X10 051211 Y7-51211 EATON ELECTRIC Copper busbar, 30x10x1500mm, untreated

Brand: EATON - MOELLER | Manufacturer Part Number: CU30X10



Manufacturer	EATON - MOELLER
MPN / Reference	CU30X10
Catalog number	Y7-51211
Category	Busbar
Minimum order	5 Pcs
Document ID	EO-CB1CC0327D
Generated	2026-08-06

Product Overview

Copper busbar, 30x10x1500mm, untreated

Copper distributor, 30x10x1500mm, untreated

Flat copper bar for CI distribution system, unhandled surface, 30x10 mm, supplied in lengths=1500mm, Ie=630A, CI distribution board up to 1000A=2x 30x10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Connection Accessories for Enclosures
--------------	---

Additional Product Information

Copper busbar, 30x10x1500mm, untreatedFlat copper bar for CI distribution system, unhandled surface, 30x10 mm, supplied in lengths=1500mm, Ie=630A, CI distribution board up to 1000A=2x 30x10

General specificationsProduct nameEaton xEffect SASY 60i copper busbar flatPart

no.CU30X10EAN4015080512110Product Length/Depth1500 millimetreProduct height10 millimetreProduct width30

millimetreProduct weight4.02 kilogramCompliancesRoHS conformCertificationsEN 13061Product TradenamexEffect SASY

60iProduct TypeCopper busbarProduct Sub TypeFlatDelivery programType60 mm system

Accessory panel building

General switchboard accessory

Modular busbar system

System for flat busbarsModelFlatAccessory/spare part typeFlat copper barsNominal current630 ATechnical Data -

ElectricalUninterrupted current (Iu) of bar360 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)

320 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

520 A (20 x 10 mm, Tu=35 °C and Ts=65 °C)

200 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

450 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)

630 A (30 x 10 mm, Tu=35 °C and Ts=65 °C) Rated operation current (Ie) 630 A Technical Data - Mechanical Unit

type Modular system Surface finishing Untreated Surface protection Untreated Material Copper, non-insulated Distance between busbar centers 60 mm Design verification as per IEC/EN 61439 - technical data Ambient operating temperature - max 35 °C

Additional information Functions System for flat busbars

Prepared enclosure

Flat busbar Special features Flat copper busbars Used with SH1005/4

System for flat bu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU30X10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.