

INDUSTRIAL COMPONENT DATA

CU-BAND6X16X0,8-BU 081222 Y7-81222 EATON ELECTRIC

Copper strip, tinned, 250A, 6x16x0.8mm, blue

Brand: EATON - MOELLER | Manufacturer Part Number: CU-BAND6X16X0,8-BU



Manufacturer	EATON - MOELLER
MPN / Reference	CU-BAND6X16X0,8-BU
Catalog number	Y7-81222
Category	Wiring band
Minimum order	1 Pcs
Document ID	EO-12D9ECE8BC
Generated	2026-08-06

Product Overview

Copper strip, tinned, 250A, 6x16x0.8mm, blue

Copper band isolated, laminated conductor E-Cu, tinned, UL approved up to max. 600VAC, insulating material heat resistant up to +105 °C, dimensions (number of layersxwidthxthickness)=6x16x0.8mm, color blue, rated operational current $I_e=250$ A, self-extinguishing according to UL 94 V0, insulation resistance to IEC 60243-1 20 kV/mm, rated operating voltage $U_e=690$ VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

Copper strip, tinned, 250A, 6x16x0.8mm, blue Copper band isolated, laminated conductor E-Cu, tinned, UL approved up to max. 600VAC, insulating material heat resistant up to +105 °C, dimensions (number of layersxwidthxthickness)=6x16x0.8mm, color blue, rated operational current $I_e=250$ A, self-extinguishing according to UL 94 V0, insulation resistance to IEC 60243-1 20 kV/mm, rated operating voltage $U_e=690$ VAC Delivery program

Product range General switchboard accessories Accessories Copper band insulated Accessories Copper band insulated

Description E-Cu laminated conductor, tin-plated

UL approved up to max. 600 V AC

Insulating material heat resistant up to +105 °C Rated voltage [U_e] 1000 V AC Rated voltage [U_e] 1500 V DC Insulation resistance 20 kV/mm Self-extinguishing to UL 94 V0 Length 2000 mm Rated operational current [I_e] 250 A Dimensions (W x H x D) 6 x 16 x 0.8 mm Cross-section 74.4 mm² Cu factor 1,32 kg Colour Blue Notes 1)Rated operational current: conform to VDE 0281

2)Cross-section: Wiring instructions for devices (e.g. terminal capacity at least ... mm²) are to be strictly observed

3)Cu factor: Calculating extra material cost Chapter General

Approvals

Product Standards UL 758; EN 60439-1, -3; CE marking UL File No. E248096 UL Category Control No. AVLV2 CSA File No. UL report applies to both US and Canada CSA Class No. - North America Certification UL listed, certified by UL for use in Canada Conditions of Acceptability max. 105 °C Specially designed for North Amer...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU-BAND6X16X0,8-BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.